

DELPHION

No active trail

Select ER

Stop Tracking

RESEARCH

PRODUCTS

INSIDE DELPHION

Log Out Work Files Saved Searches

My Account

Search: Quick/Number Boolean Advanced Derwent

Help

The Delphion Integrated ViewGet Now: ☒ PDF | [File History](#) | [Other choices](#)Tools: Add to Work File: [Create new Work File](#)

Add

View: [INPADOC](#) | Jump to: [Top](#) Go to: [Derwent](#)☒ [Email this to a friend](#)Title: **JP63013282A2: NONAQUEOUS ELECTROLYTE SECONDARY BATTERY**Derwent Title: Electrode useful for non-aq. secondary batteries - consists of graphite-like carbon deposited from gas phase [\[Derwent Record\]](#)

Country: JP Japan

Kind: A (See also: JP06003745B4)

Inventor: **TAJIMA YOSHIMITSU;
MORI MOTOO;
TANAKA HIDEAKI;**Assignee: **SHARP CORP**
[News, Profiles, Stocks and More about this company](#)Published / Filed: **1988-01-20 / 1986-07-02**Application Number: **JP1986000156966**

IPC Code: Advanced: C01B 31/02; C23C 16/26; H01M 4/58; H01M 4/96; H01M 10/40;

Core: C01B 31/00; H01M 10/36; more...

IPC-7: H01M 4/60; H01M 10/40;


Priority Number: 1986-07-02 JP1986000156966

Abstract: PURPOSE: To increase charge-discharge cycle performance, to limit discharge capacity by that of a negative electrode, and to widen the range of usable materials by making the charge-discharge capacity of a positive electrode larger than that of a negative electrode in a nonaqueous electrolyte secondary battery comprising a positive electrode, a nonaqueous electrolyte, and a negative electrode using a specific carbon as active material.

CONSTITUTION: As a negative electrode of a secondary battery using nonaqueous organic solvent, a carbon body mainly comprising carbon which is formed from a hydrocarbon compound by vapor phase build-up method by low temperature heat decomposition at 1500°C or lower and has planar net-like six-membered ring structure (graphite structure) having disorder layer structure and selective orientation structure is used, and the capacity of the negative electrode is made smaller than that of a positive electrode. A main planar spacing of the carbon is 0.337~0.355nm. The ratio of Raman strength 1360cm⁻¹, to Raman strength of 1580cm⁻¹ in Raman structure is 0.4~1.0. V2O5, Cr2O3, chalcogen compound, and composite or mixture of these compounds are used in the positive electrode.

COPYRIGHT: (C)1988,JPO&Japio

INPADOC None

Get Now: [Family Legal Status Report](#)[View Image](#)

1 page

Legal Status:

Designated DE FR GB


Country:

Family: [Show 16 known family members](#)

Forward

References:

Go to Result Set: Forward references (1)

PDF	Patent	Pub.Date	Inventor	Assignee	Title
	US6706447	2004-03-16	Gao; Yuan	FMC Corporation, Lithium Division	Lithium metal dispersion in secondary battery anodes

Other Abstract
Info:

CHEMABS 108(10)078670M DERABS C87-272820

[Nominate this for the Gallery...](#)

THOMSON

Copyright © 1997-2006 The Thomson Corporation

[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)